

Narrow Frame Patio Door

Air-Water-Structural Performance



Type	Size	Reinforcement Code	Air Infiltration	Operating Force	Water Penetration	Uniform Load	Overall Rating	Report Number
Door Picture Window	107.25 x 47.5	00	0.01 scfm/ft ²	N/A	7.50 psf	± 75.0 psf	F-R50	B7917.01
Patio Door	107.25 x 79.5	H5	0.10 scfm/ft ²	9 lbf	6.75 psf	± 67.5 psf	SD-R45	D2903.01
Patio Door	107.25 x 79.5	E5	0.11 scfm/ft ²	13 lbf	4.50 psf	± 45.0 psf	SD-R30	D2901.01
Patio Door	71.25 x 79.5	H5	0.16 scfm/ft ²	16 lbf	7.50 psf	± 75.0 psf	SD-R50	D3268.01
Patio Door	71.25 x 79.5	E5	0.17 scfm/ft ²	16 lbf	5.25 psf	± 52.5 psf	SD-R35	D2892.01
Patio Door	71.25 x 95.5	H5	0.09 scfm/ft ²	14 lbf	5.25 psf	± 52.5 psf	SD-R35	D3269.01
Patio Door	77.25 x 83.5	E5	0.15 scfm/ft ²	13 lbf	4.50 psf	± 45.0 psf	SD-R30	D3264.01
Patio Door	95.25 x 79.5	H5	0.11 scfm/ft ²	12 lbf	7.50 psf	± 75.0 psf	SD-R50	B7598.01
Patio Door	95.25 x 79.5	E5	0.15 scfm/ft ²	11 lbf	5.25 psf	± 52.5 psf	SD-R35	C3516.01

TEST REPORTS ARE AVAILABLE UPON REQUEST

All units tested in accordance with AAMA/WDA/CSA 101/I.S.2/A440-08, and include a welded corner test, for which all units either met or exceeded the standards, and a deglazing test, for which all units either met or exceeded the standards.

- 1) Sizes are certified up to and including the sizes listed.
- 2) Air infiltration is based upon static pressure of 1.57 psf (25 mph). Air infiltration shall not exceed 0.3 standard cubic feet per minute (scfm) per square foot.
- 3) Operating force listed is an average of the forces required to open and close the unit. The maximum allowable pound force is 30 lbf for vertical sliders and 20 lbf for horizontal sliders.
- 4) The minimum water resistance is 2.86 psf for an entry level R15 water rating, 3.75 psf for an entry level LC25 water rating, and 4.50 psf for an entry level C30 water rating.
- 5) The minimum structural test pressure is 22.5 psf for an entry level R15 structural rating, 37.5 psf for an entry level LC25 structural rating, and 45.0 psf for an entry level C30 structural rating.

NOTES:

SPECIAL MANUFACTURING REQUIREMENTS (FOR EXAMPLE: REINFORCEMENT, GLASS STRENGTH, ETC.) MAY BE NECESSARY TO MEET THE DESIGN PRESSURE LISTED.

PLEASE SPECIFY DESIGN PRESSURE REQUIRED WHERE APPLICABLE.

PLEASE CONSULT YOUR SIMONTON REPRESENTATIVE FOR AVAILABILITY OF SIZES. FACTORS SUCH AS HARDWARE RELIABILITY, SHIPPING, CONSISTENCY IN OPERATING FORCE AND SECURING THE UNIT PROPERLY MAY LIMIT THE UNIT SIZE.