

ARCHITECTURAL SERIES

| Glass Package | R-Value | U-Factor | Gain Coefficient | Visible Transmittance |
|--------------------|---------|----------|------------------|-----------------------|
| AWNING | | | | |
| HP | 3.13 | 0.32 | 0.27 | 0.48 |
| HPSC | 3.13 | 0.32 | 0.2 | 0.38 |
| HP2+ | 3.45 | 0.29 | 0.26 | 0.47 |
| HP2+SC | 3.45 | 0.29 | 0.2 | 0.37 |
| CASEMENT | | | | |
| HP | 3.13 | 0.32 | 0.27 | 0.48 |
| HPSC | 3.13 | 0.32 | 0.2 | 0.38 |
| HP2+ | 3.57 | 0.28 | 0.26 | 0.47 |
| HP2+SC | 3.57 | 0.28 | 0.19 | 0.37 |
| DOUBLE HUNG | | | | |
| HP | 2.7 | 0.37 | 0.28 | 0.51 |
| HPSC | 3.03 | 0.33 | 0.21 | 0.4 |
| HP2+ | 3.33 | 0.3 | 0.27 | 0.49 |
| HP2+SC | 3.33 | 0.3 | 0.2 | 0.39 |

Additional glass packages are available, please consult your Ply Gem representative for complete details.