



DaylightMax Picture Window

Without Grids

Insulated Glass Unit Package	Low E Type	Gas	Spacer System	IG Thickness	Panels of Glass	U-Factor	R-Value	Solar Heat Gain Coefficient	Visible Transmittance	UV Block
						Total Unit	Total Unit	Total Unit	Total Unit	Center of Glass
Standard	ProSolar	Argon	Intercept	3/4"	2	0.27	3.70	0.34	0.62	73%
1/8" over 3/16"	ProSolar	Argon	Super Spacer	3/4"	2	0.26	3.85	0.34	0.62	73%
ENERGY STAR Northern	ProSolar Sun	Argon	Supercept	3/4"	2	0.28	3.57	0.57	0.70	71%
ENERGY STAR North Central	ProSolar	Argon	Supercept	3/4"	2	0.26	3.85	0.34	0.62	73%
ENERGY STAR South Central	ProSolar Shade	Argon	Supercept	3/4"	2	0.26	3.85	0.24	0.57	92%
ENERGY STAR Southern	ProSolar Shade	Argon	Intercept	3/4"	2	0.26	3.85	0.24	0.57	92%
ETC Starter 366	ProSolar Shade	Argon	Intercept	3/4"	2	0.26	3.85	0.24	0.57	92%
Title 24	ProSolar Shade	Argon	Intercept	3/4"	2	0.26	3.85	0.24	0.57	92%

With Grids

Insulated Glass Unit Package	Low E Type	Gas	Spacer System	IG Thickness	Panels of Glass	U-Factor	R-Value	Solar Heat Gain Coefficient	Visible Transmittance	UV Block
						Total Unit	Total Unit	Total Unit	Total Unit	Center of Glass
Standard	ProSolar	Argon	Intercept	3/4"	2	0.27	3.70	0.31	0.56	73%
1/8" over 3/16"	ProSolar	Argon	Super Spacer	3/4"	2	0.28	3.57	0.31	0.55	73%
ENERGY STAR Northern	ProSolar Sun	Argon	Supercept	3/4"	2	0.28	3.57	0.52	0.63	71%
ENERGY STAR North Central	ProSolar	Argon	Supercept	3/4"	2	0.26	3.85	0.31	0.56	73%
ENERGY STAR South Central	ProSolar Shade	Argon	Supercept	3/4"	2	0.26	3.85	0.22	0.51	92%
ENERGY STAR Southern	ProSolar Shade	Argon	Intercept	3/4"	2	0.26	3.85	0.22	0.51	92%
ETC Starter 366	ProSolar Shade	Argon	Intercept	3/4"	2	N/A	N/A	N/A	N/A	92%
Title 24	ProSolar Shade	Argon	Intercept	3/4"	2	0.26	3.85	0.22	0.51	92%

Please consult your Simonton Representative for additional glass package offerings.

Links of Interest:

[Energy-efficient Windows and Doors](#)

[Glossary of Terms](#)

<http://nfrfc.org>

<https://www.energystar.gov/>

<http://efficientwindows.org/understanding.php>

Note:

The thermal data is based on standard unit options; change in Performance Rating (DP) may require an insulated glass package upgrade.