

Table of Gliding (Sliding) Window Sizes

Scale 1/8" = 12" – 1:96


Exterior J-Channel Dimension	25"	37"	49"	51"	55"	61"	65"	73"
Window Dimension	24"	36"	48"	50"	54"	60"	64"	72"
Minimum Rough Opening	24 1/2"	36 1/2"	48 1/2"	50 1/2"	54 1/2"	60 1/2"	64 1/2"	72 1/2"
Unobstructed Glass (single sash only)	9 1/8"	15 1/8"	21 1/8"	22 1/8"	24 1/8"	27 1/8"	29 1/8"	33 1/8"

CUSTOM WIDTHS – 16" to 52"

CUSTOM HEIGHTS – 24" to 84"

20"	2018	3018	4018	4218	4618	5018	5418	6018
24"	2020	3020	4020	4220	4620	5020	5420	6020
36"	2030	3030	4030	4230	4630	5030	5430	6030 ^o
42"	2036	3036	4036	4236	4636	5036 ^o	5436 ^o	6036 ^o
44"	2038	3038	4038	4238	4638 ^o	5038 ^o	5438 ^o	6038 ^o
46"	20310	30310	40310	42310	46310 ^o	50310 ^o	54310 ^o	60310 ^o
48"	2040	3040	4040	4240 ^o	4640 ^o	5040 ^o	5440 ^o	6040 ^o
50"		3042	4042	4242 ^o	4642 ^o	5042 ^o	5442 ^o	6042 ^o
52"		3044	4044	4244 ^o	4644 ^o	5044 ^o	5444 ^o	6044 ^o
54"		3046	4046	4246 ^o	4646 ^o	5046 ^o	5446 ^o	6046 ^o
60"		3050	4050	4250 ^o	4650 ^o	5050 ^o	5450 ^o	6050 ^o

Custom-size windows are available in 1/8" increments.



Active-Stationary


Gliding window includes a nailing flange and J-channel.

Grille pattern and number of lights varies with window size.

Custom Sizes & Specification Formulas

Available in 1/8" increments between minimum and maximum widths and heights shown. Some restrictions apply.

Gliding (Sliding) Windows



Clear Opening	Width = (window width + 2) - 5" Height = window height - 5.125"	Minimum R.O.	Width = window width + 1/2" Height = window height + 1/2"
Vent Opening	Width = (window width + 2) - 5" Height = window height - 5.125"	Unobstr. Glass	Width = (window width + 2) - 2.875" Height = window height - 5"

- "Window Dimension" always refers to inside frame to frame dimension.
- **"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.**
- ♦ Meet or exceed clear opening area of 5.7 sq.ft., clear opening width of 20" and clear opening height of 24".

- **Clear Opening** formulas provide dimensions for determining area available for egress.
- **Vent Opening** formulas provide dimensions for determining area available for passage of air.
- **Minimum R.O.** (minimum rough opening) formulas provide minimum rough opening width and height dimensions.
- **Unobstr. Glass** (unobstructed glass) formulas provide dimensions for determining area available for passage of light.