



1

†

Table of Triple Double-Hung Window Sizes (Vinyl Market Sizing)

Scale $\frac{1}{8}$ " = 12" - 1:96

	xterior "J" C imension	channel			54 3/4"	60 3/4"	72 3/4"	84 3/4"	90 3/4"	963/4"	†		1083/4"	_
	/indow Dim	ension			53 1/4"	59 1/4"	71 1/4"	83 1/4"	89 1/4"	95 1/4"			107 1/4"	
	linimum ough Open	ning			53 3/4"	59 3/4"	71 3/4"	83 3/4"	89 3/4"	95 3/4"			1073/4"	1
Uı	nobstructeo	d Glass			11 9/16"	13 9/16"	17 9/16"	21 9/16"	23 9/16"	25 ⁹ /16"			29 %16"	_
(10	mor saon only)				CUSTOM WIDTHS -	- 57 ½" to 107 ½"								
37 1/2"	36"	36 1/2"	14 13/16"	30" to 76 3/4"	1630	1830	2030	2430	2630	↓ ↓ ↓ ↑ ↑ 1 1 1 1 1 2830		↓	↓ ↑ 3030	
39 1/2"	38	38 1/2"	15 13/16"	CUSTOM HEIGHTS – 3	1632	1832	2032	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2632	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		†	↓ ↑ 3032	
45 1/2"	44"	44 1/2"	18 13/16"	CUSTOM		+ + + + + + + + + + + + + + + + + + +	↓ ↓ ↓ ↑ ↑ ↑	↓ ↓ ↓ ↑ ↑ ↑		↓ ↓ ↑ ↑		+	+	
47 1/2"	46"	461/2"	19 13/16"		1638	1838	2038	2438	2638	2838		+	3038 ↓	
+	<u> </u>	•			16310	18310	20310	24310	26310	28310			30310	
49 1/2"	48"	48 1/2"	20 13/16"		† † †	† † †	↓ ↓ ↓	↓ ↓ ↓ ↑	↓ ↓ ↓	↓ ↓ ↓ ↑		†	+	
1	-		+		1640	1840	2040	2440	2640	2840			3040	<u>] L</u>
511/2"	50"	501/2"	13/16"		+ + +	+ + +	+ +	+ + +	+ +	+ + +		1	+	\prod
51		2(21		† † †	† † †	† † † †	† † † †	† † † † †	† † † †		1	↑	
•		-	-		1642	1842	2042	2442	2642	2842			3042	11 15
53 1/2"	52"	52 1/2"	22 13/16"		+ + +	+ + +	+ + +	↓ ↓ ↓	↓ ↓ ↓	↓ ↓ ↓		+	+	
			2		1011	1001	† † †	† † †	<u>†</u> † †	† † †		1	1	
1					1644	1844	2044	2444	2644	2844			3044	П
55 1/2"	54"	54 1/2"	23 13/16"		† † † † † † † † † † † † † † † † † † †	+ + +	↓ ↓ ↓ ↓	† † † † † †	↓ ↓ ↓	↓ ↓ ↓ ↓		†	+	
			\vdash		1646	1846	2046	2446	2646	2846			3046	
,5"	_	.5"	13/16"			+ + +	+ + +	+ + +	+ + +	+ + +		+	+	
61 1/2"	.09	60 1/2"	26 13/		1 1	1 1 1	† † †	† † †	† † †	† † †		†	†	
•					1650	1850	2050	2450	2650	2850			3050◊	,
63 1/2"	62"	62 1/2"	27 13/16"		+ + +	+ + +	+ + +	+ + +	+ + +	→ → →		+	+	
63	9	62	273		1	1 1 1	† † †	† † † †	† † †	† † † †		1	1	
					1652	1852	2052	2452	2652	2852			3052 ◊)

Custom-size windows are available in 1/4" increments.

Triple double-hung windows include a nailing flange and optional J-channel.

Windows have one continuous frame.

Grille pattern and number of lights varies with window size.

^{• &}quot;Window Dimension" always refers to inside frame to frame dimension.

^{• &}quot;Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

^{• &}quot;Window Dimension" always refers to inside frame to frame dimension.

^{• &}quot;Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Meet or exceed clear opening area of 5.7 sq.ft., clear opening width of 20" and clear opening height of 24".





108 3/4"

107 1/4"

1073/4"

29 9/16"

3056◊

3060◊

†

+

†

+

Table of Triple Double-Hung Window Sizes

Scale $\frac{1}{8}$ " = 12" - 1:96

Exterior "J" Channel Dimension				54 3/4"	60 3/4"	72 3/4"	843/4"	90 3/4"	963/4"				
Window Dimension						53 1/4"	59 1/4"	71 1/4"	83 1/4"	89 1/4"	95 1/4"		
Minimum Rough Opening				53 3/4"	59 3/4"	71 3/4"	83 3/4"	89 3/4"	95 3/4"				
Unobstructed Glass (lower sash only)				11 9/16"	13 9/16"	17 9/16"	21 9/16"	23 9/16"	25 9/16"				
					(CUSTOM WIDTHS - 57 ¹ / ₄ " to 107 ¹ / ₄ "							
67 1/2"	.99	661/2"	:	29 13/16"	30" to 76 3/4"	+ + +	+ + +	+ + +		+ + +	+ + +		
				\perp	HTS -	1656	1856	2056	2456	2656	2856		
73 1/2"	72"	72 1/2"	:	32 13/16"	CUSTOM HEIGHTS	+ + +	+ + +	+ + +	+ + +	+ + +	+ + +		
73		72		37	ಶ	† † †	† † †	† † †	↑ ↑	† † †	† † †		
1	•		•	-		1660	1860	2060	2460	2660◊	2860♦		
75 1/2"	74"	74 1/2"	=	33 13/16"		+ + +	† † †	† † †	† † †	→ → →	↓ ↓ ↓ ↑ ↑ ↑		
•	•			—		1662	1862	2062	2462	2662◊	2862◊		

Custom-size windows are available in 1/4" increments.

Triple double-hung windows include a nailing flange and optional J-channel.

Windows have one continuous frame.

Grille pattern and number of lights varies with window size.

Custom-size windows are available in 1/4" increments.

Triple double-hung windows include a nailing flange and optional J-channel.


Windows have one continuous frame.

Grille pattern and number of lights varies with window size.

- "Window Dimension" always refers to inside frame to frame dimension.
- "Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
- Meet or exceed clear opening area of 5.7 sq.ft., clear opening width of 20" and clear opening height of 24".

Custom Sizes & Specification Formulas

Triple Double-Hung Windows



Available in 1/4" increments between minimum and maximum widths and heights shown. Some restrictions apply.

Clear Opening	width = (window width \div 3) $-$ 3.563" Height = (window height \div 2) $-$ 4.063"	Minimum R.O.	$ \mbox{Width} = \mbox{window width} + \mbox{$1/2$"} $
Vent Opening	width = (window width \div 3) - 3.563" Height = (window height \div 2) - 4.063"	Unobstr. Glass	Width = (window width \div 3) $-$ 6.188" Height = (window height \div 2) $-$ 3.188"

- Clear Opening formulas provide dimensions for determining area available for egress.
- Vent Opening formulas provide dimensions for determining area available for passage of air.
- Minimum R.O. (minimum rough opening) formulas provide minimum rough opening width and height dimensions.
- Unobstr. Glass (unobstructed glass) formulas provide dimensions for determining area available for passage of light.

©2021 American Craftsman, part of the Cornerstone Building Brands family. ALL RIGHTS RESERVED. REVA/0721

^{• &}quot;Window Dimension" always refers to inside frame to frame dimension.

^{• &}quot;Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

[•] Meet or exceed clear opening area of 5.7 sq.ft., clear opening width of 20" and clear opening height of 24".