DOUBLE-HUNG WINDOWS - 70 Series



Table of Triple Double-Hung Window Sizes (Wood Market Sizes)

Scale $\frac{1}{8}$ " = 12" - 1:96

Scale $\frac{1}{8}$ " = 12" $-$ 1:96					
	60 3/4" 66 3/4"	78 3/4"	90 3/4"	102 3/4"	108 3/4"
Window Dimension	59 1/4" 65 1/4"	77 1/4"	89 1/4"	101 1/4"	107 1/4"
Minimum Rough Opening	59 3/4" 65 3/4"	77 3/4"	89 3/4"	101 3/4"	107 3/4"
Unobstructed Glass	13 9/16" 15 9/16"	19 9/16"	23 9/16"	27 9/16"	29 9/16"
(lower sash only)	CUSTOM WIDTHS - 57 1/4" to 107 1/4"	'			
38 3/4" 36 3/4" 37 1/4" 15 3/16" 30" to 76 3/4"			1 1 1 1	↓ ↓ ↓ ↑ ↑ ↑	↓ ↓ ↑ ↑
	16210 18210	20210	24210	28210	210210
40 40 17:	† † † † † † † 1	2032	2432	† † † † 1	† † † † 21032
501/4" 48 34" 49 1/4" 21 3/16"	1992 1892	+ + +	1 1 1 1	+ + +	+ + +
48 49 49 21 3	1 1 1 1	† † †	† † †	† † †	† † †
· · · · · · · · · · · · · · · · · · ·	16310 18310	20310	24310	28310	210310
54 1/4" 52 3/4" 53 1/4" 23 3/16"	+ + + + +	+ + +	+ + +	+ + +	+ + +
		1 1 1	1 1 1 1	1 1 1	1042
	1642 1842	2042	2442	2842	21042
58 1/4" 56 3/4" 57 1/4" 25 3/16"		+ + +	+ + +	+ + +	+ + +
	1646 1846	2046	2446	2846	21046
66 1/4" 64 3/4" 65 1/4" 29 3/16"	+ + + + + +	+ + +	+ + +	+ + +	+ + + +
53		† † †	† † †	† † † †	† † † † †
	1652 1852	2052	2452	2852�	21052�
68 3/4" 69 1/4" 31 3/16"	+ + + + +	+ + +	+ + +	+ + +	+ + +
69 69 31 3	† † † † † † †	† † †	† † † †	† † †	† † †
	1656 1856	2056	2456	2856◊	21056�
4" 4" 16" 16" 16" 1	+ + + +	+ + +	+ + +	+	+ + +
74 1/4" 72 3/4" 73 1/4" 33 3/16"	1 1 1 1 1	† † † †	† † †	† † †	† † †
	16510 18510	20510	24510 ◊	28510�	210510\$
4" 4" 16"	+ + + +	+ + +	+ + +	+ + +	+ + +
78 1/4" 76 3/4" 77 1/4" 35 3/16"	+ + + + +	† † †	1 1	† † †	† † †
	1662 1862	2062	2462◊	2862 ◊	21062�

^{• &}quot;Window Dimension" always refers to inside frame to frame dimension.



DOUBLE-HUNG WINDOWS - 70 Series

Custom-size windows are available in 1/4" increments.


Triple double-hung windows include a nailing flange and optional J-channel.

Windows have one continuous frame.

Grille pattern and number of lights varies with window size.

Custom Sizes & Specification Formulas

Triple Double-Hung Windows



Available in 1/4" increments between minimum and maximum widths and heights shown. Some restrictions apply.

Clear Opening	Width = (window width \div 3) - 3.563"	Minimum R.O.	width = window width + 1/2"
++	Height = (window height ÷ 2) - 4.063"		Height = window height + 1/2"
Vent Opening	Width = (window width \div 3) - 3.563"	Unobstr. Glass	Width = (window width ÷ 3) - 6.188"
+++	Height = $\left(\text{window height} \div 2\right) - 4.063"$	4 + + + + + + + + + + + + + + + + + + +	Height = (window height ÷ 2) - 3.188"

- Clear Opening formulas provide dimensions for determining area available for egress.
- Vent Opening formulas provide dimensions for determining area available for passage of air.
- Minimum R.O. (minimum rough opening) formulas provide minimum rough opening width and height dimensions.
- Unobstr. Glass (unobstructed glass) formulas provide dimensions for determining area available for passage of light.

©2021 American Craftsman, part of the Cornerstone Building Brands family. ALL RIGHTS RESERVED. REVA/0721

^{• &}quot;Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.

Meet or exceed clear opening area of 5.7 sq.ft., clear opening width of 20" and clear opening height of 24".